

GREENTECH LED

LED Lighting & Fixture Specialist

www.greentechled.com

sales@greentechled.com

Phone: 1-408-444-5338

TROFFER RETROFIT FIXTURE. (2X2.2X4) (Remodel fixture)

*** US Patented Product ***

SPECIFICATIONS:

Voltage Rating: 120-277Volt

50~60Hz PF: >0.95

CRI: >72 THD: <20%

Power Consumptions: 40 watt ±5%

CCT: 3000.4000.5000K

Lumens: > 127 per watt

Dimmable: 0-10V

Beam Angle: 120°

Rating: Indoor

Average Life: 50,000 Hour

Including: Earthquake safety cable

3-5 years limited factory warranty

Available: Single lens & Double Lens

Models: Center basket

Certified: ETL and DLC

Option: Motion sensor, Microwave sensor,

Option: Emergency power backup

MODEL NUMBER:

(Single Lens)

GTL-LMS-RET-22-S-40W-4K

GTL-LMS-RET-24-S-40W-4K

(Double Lens)

GTL-LMS-RET-22-D-40W-4K

GTL-LMS-RET-24-D-40W-4K

US Patented Product



\$ keep the existing fixture just installed the new retrofit fixture (It is take 5 minutes for installation)
Saving time and labor cost.

±